

TECHNICAL DATA

Restorator DUO® Dual-Powered, Odor-Neutralizing System

*The Superior **Alternative** to Ozone Generators*



Replaceable, nontoxic natural essential oil cartridges. 3X Industrial & S.O.S. recommended. (sold separately)



SUGGESTED APPLICATIONS

- ◆ Fire/Flood Damage Restoration
- ◆ Vehicle/RV/Boat
- ◆ Contents Restoration
- ◆ Smoke Contaminated Hotel Rooms

- ◆ Real Estate/Foreclosures
- ◆ Crime Scene/Bioremediation
- ◆ Disaster Recovery
- ◆ Athletic Facilities

IMPORTANT

This system provides a safe, effective *alternative* to ozone. It is *not* recommended for use with ozone generating equipment.

Use Xactimate codes: CLN DODRM, CLN DODRME, & CLN DODRMEM

Proudly made in the USA



Pioneering Simple Solutions for Tough Odors Naturally Since 1979

Introducing the Restorator DUO[®]

Dual-Powered for Versatile Odor Control

PURPOSE

The Restorator DUO is a rechargeable, easy-to-use, portable system. Put the battery-powered unit to work where electrical power has been interrupted or is not easily accessible. It treats areas up to 20,000 ft³ to effectively eliminate odor contamination quickly and safely. Primarily intended for delivering a fast, high-intensity treatment, it uses Vaportek's patented spill-proof essential oil membranes to release a nontoxic, odor-neutralizing dry vapor into the air. Penetrating vapor quickly controls and eliminates malodor caused by smoke, humidity, food, and biological odors, among others. Based on proven technology originally developed for use in medical facilities, the Restorator DUO sets the standard for treating an area's atmosphere, structure, and contents simultaneously.

PLACEMENT

The innovative Restorator DUO is intended for application where quick results are desired. To be used in areas with or without electrical power. Place on a firm, stable surface, situating the unit so air flow at both ends is unobstructed, preferably in a relatively high location. Deodorization may require as little as 15-60 minutes for light contamination. For more severe contamination, treatment may take several hours or days. If necessary, move the unit to different areas. As with any electrical device, do not locate or use near water. For best results, store cartridges in a cool, dry location and keep away from extreme heat. Dry vapor output will be affected by humidity, airflow, and temperature. Ideal dry vapor release occurs at 50-80°F. Vapor release significantly increases in excess of 90°F.

DETAILS

Easy portability and durable lightweight polypropylene construction. No evacuation or recovery period is required with Vaportek technology. Not designed for continuous, long-term operation. Cartridge life is approximately 270 hours. The system does *not* create moisture or ozone, and will not harm fabric, plants, rubber, adhesives, electrical components, or remove pigment from leather. Vaportek products use natural essential oils. If an allergic reaction occurs, please discontinue use immediately. Dimensions: 7"H x 6"W x 10"L. Weight: 2 lbs., 4 oz. Five year limited warranty.

✓ **Works Fast**
Odor neutralizer is immediate & permanent.

✓ **Easy-to-Use**
Just uncap the cartridge, insert into machine, & turn on.

✓ **Safe & Environmentally Preferable**
No chemicals or harmful ozone.

✓ **Rechargeable Battery**
Fully charged unit runs for 18+ hours.



“The DUO worked great. It got the odor out & it was nice to not have to run a cord.”
—Interlink Supply



“Using the DUO is quite easy. Simple.”
—Bridgepoint

Reorder Information:

Restorator DUO (#90-5400)
S.O.S./Smoke Odor Solution cartridge (#90-5150-85)
3X Industrial cartridge (#90-5150)
Battery pack included. Backup battery packs (#11-2148)
AC charger included. Backup AC charger (#11-2151)

NOTE: Because we are committed to improving our products, Vaportek reserves the right to change product specifications and/or availability without notice or obligation.



VAPORTEK[®]

P: 800.237.6367 | F: 262.246.5065

www.vaportek.com

www.facebook.com/vaportek

www.linkedin.com/vaportek

Sussex, WI USA